



MODEL	HOLE SIZE		'A' THREAD	'B'	'C'	'D'	'E'	APPLIED LOAD (KN)
	From	To						@1300 Bar
								Per bolt
<b>E1</b>	40	44	M33x3.5	67	51	58	91	321
<b>E2</b>	45	47	M36x4	72	54	62	95	346
<b>E3</b>	48	51	M39x4	79	60	66	109	474
<b>E4</b>	52	54	M42x4.5	84	63	72	114	498
<b>E5</b>	55	58	M45x4.5	89	67	76	121	584
<b>E6</b>	59	63	M48x5	96	72	82	128	645
<b>E7</b>	64	68	M52x5	104	78	89	138	805
<b>E8</b>	69	72	M56x5.5	110	82	96	148	973
<b>E9</b>	73	78	M60x5.5	115	88	102	159	1066
<b>E10</b>	79	83	M64x6	123	94	108	167	1186
<b>E11</b>	84	87	M68x6	129	98	116	178	1463
<b>E12</b>	88	93	M72x6	137	104	122	188	1585
<b>E14</b>	94	97	M76x6	143	108	130	199	1771
<b>E15</b>	98	103	M80x6	152	116	136	211	2039
<b>E16</b>	104	109	M85x6	161	123	146	223	2250
<b>E17</b>	110	116	M90x6	170	129	154	237	2600
<b>E18</b>	117	121	M95x6	179	136	164	255	3114
<b>E19</b>	123	129	M100x6	187	142	172	263	3229
<b>E20</b>	130	135	M105x6	199	152	182	277	3734
<b>E21</b>	136	140	M110x6	208	158	190	291	4086
<b>E22</b>	141	146	M115x6	217	165	198	301	4481
<b>E23</b>	147	150	M120x6	225	171	208	321	4989